



# Heyco® Snap Bushings

Mounting Hole Diameter Range: 1.000" (25,4 mm) to 6.0" (152,4 mm)

MOUNTING HOLE DIAMETER		PART NO.		DESCRIPTION	PART DIMENSIONS					
in.	mm.	Black	White		A Inside Diameter		B Head Diameter		C Overall Height	

**Multiple Locking Steps for Panel Thickness up to .125" (3,2 mm)**


1.000	25,4	<b>2140</b>	<b>2141</b>	SB 1000-12	.766	19,4	1.125	28,6	.453	11,5
1.093 - 1.125	27,8 - 28,6	<b>2160</b>	<b>2161</b>	SB 1093-13	.812	20,6	1.218	30,9	.453	11,5
		<b>2163</b>	<b>2164</b>	SB 1093-14	.875	22,2				
		<b>2166</b>	<b>2167</b>	SB 1093-15	.937	23,8				
1.187	30,2	<b>2182</b>	<b>2183</b>	SB 1187-15	.937	23,8	1.312	33,3	.453	11,5
1.250	31,8	<b>2198</b>	<b>2199</b>	SB 1250-15	.937	23,8	1.359	34,5	.453	11,5
		<b>2201</b>	<b>2202</b>	SB 1250-16	1.000	25,4				
1.375	34,9	<b>2207</b>	<b>2208</b>	SB 1375-14	.875	22,2	1.490	37,3	.453	11,5
		<b>2210</b>	<b>2211</b>	SB 1375-16	1.014	25,8				
		<b>2233</b>	<b>2234</b>	SB 1500-17	1.062	27,0				
1.500	38,1	<b>2236</b>	<b>2237</b>	SB 1500-18	1.125	28,6	1.609	40,9	.453	11,5
		<b>2240</b>	<b>2241</b>	SB 1500-21	1.312	33,3				
		<b>2300</b>	<b>2301</b>	SB 1750-22	1.375	34,9				
1.750	44,5	<b>2400</b>	<b>2401</b>	SB 2000-26	1.640	41,6	2.125	54,0	.453	11,5
		<b>2406</b>	<b>2414</b>	SB 2000-28	1.750	44,5				

**Multiple Locking Steps for Panel Thickness up to .250" (6,4 mm)**

2.093	53,1	<b>2415</b>	<b>2416</b>	SB 2.093-29	1.813	46,0	2.350	59,7	.720	18,3
2.250	57,2	<b>2417</b>	<b>2418</b>	SB 2.250-29	1.860	47,1	2.480	63,1		
2.500	63,5	<b>2420</b>	<b>2421</b>	SB 2.500-31	1.970	50,0	2.660	67,5		
3.000	76,2	<b>2461</b>	<b>2462</b>	SB 3.000-39	2.470	62,7	3.150	80,0	.750	19,1
		<b>2424</b>	<b>2425</b>	SB 3.000-44	2.750	69,9	3.160	80,2	.720	18,3
3.375	85,7	<b>2407</b>	<b>2408</b>	SB 3.375-45	2.812	71,4	3.660	93,0	.720	18,3
3.500	88,9	<b>2470</b>	<b>2471</b>	SB 3.500-47	2.940	74,7				
4.000	101,6	<b>2479</b>	<b>2480</b>	SB 4.000-55	3.470	88,1	4.150	105,4	.740	18,8
5.000	127,0	<b>2409</b>	<b>2410</b>	SB 5.000-70	4.375	113,8	5.219	132,6		
6.000	152,4	<b>2484</b>	<b>2485</b>	SB 6.000-86	5.375	139,2	6.219	157,9		



Standard colors black and white. Consult Heyco for other colors.



Quick Specs

Material: Nylon 6/6  
 Certifications: Recognized under the Component Program of Underwriters' Laboratories, File E15331  
 Certified by Canadian Standards Association, File 8919  
 Flammability Rating: 94V-2  
 Material Temperature Index: 257°F (125°C)–Maximum temperature on part not to exceed 221°F (105°C)